

REPEATER



Extend the range of the Sigfox network.





- Extend the range of the
 Sigfox network: meter, building management, trade...
- Repeat service for upload messages (unsupported top-down)

BENEFITS



- Indoor or Outdoor (IP67), even in a constrained environment
- · For all types of Sigfox RC1 network sensors
- Several modes for setting the WhiteList (local or remote)
- Easy to install: battery-operated product
- · A dedicated application for better control

EXAMPLE OF USE CASE

Place one or more adeunis Repeaters to optimise Sigfox network coverage in the following examples of usage:





Smart Building - Boiler room


Your transmitters are installed on meters located indoors, underground, where network coverage may be limited.



Smart City - Parking

Your transmitters are installed inside a parking area, where the concrete, the basement... limit the network's range.







Smart Industry - Rural area

Your transmitters are installed in a warehouse located in a rural area. Here the network exists but it may be at the limits of the Sigfox antenna's range.

TECHNICAL SPECIFICATIONS

- · Interchangeable battery
- · Range: up to 300m in outdoor and 50m in indoor
- · Zone: RC1
- · Dimensions: 185 x 50 x 27mm
- Operating temperature: -25°C / +70°C

- · Weight: 135g
- · Case: IP67
- · Integrated fixation system: DIN-Rail, tube, wall, necklace
- · Standard: Directive 2014/53/UE (RED)

